

T.J. RONAN PAINT CORP.  
SAFETY DATA SHEET  
FOR PROFESSIONAL GRAPHIC ARTS COATINGS

## 1. Product Identification

MANUFACTURER'S NAME: T.J. RONAN PAINT CORP.  
749 EAST 135TH. STREET  
BRONX, NEW YORK 10454

INFORMATION PHONE: (718) 292-1100 DATE: 5/19/16

EMERGENCY PHONE: (800) 424-9300 CHEMTREC

PRODUCT CLASS: JAPAN COLOR

PRODUCT NAME:

AMERICAN VERMILION	PERMANENT BLUE
BULLETIN BLUE	PERMANENT STRIPING WHITE
BULLETIN RED	POSTER RED
BURNT SIENNA	PRUSSIAN BLUE
BURNT UMBER	RAW SIENNA
C.P. GREEN L, M, D	RAW UMBER
CHROME YELLOW LL, L, M	REFINED LAMPBLACK
CHROME YELLOW O	ROSE PINK
COBALT BLUE	SIGNCRAFT RED
DROP BLACK	SOLID COVERING LAMPBLACK
EMERALD GREEN	TURKEY RED
FLAKE WHITE	ULTRAMARINE BLUE
FRENCH YELLOW OCHRE	VAN DYKE BROWN
FRENCH ZINC WHITE	VENETIAN RED
LIBERTY RED M	

## 2. Hazards Identification

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

### GHS Classification

Flammable Liquids - Category 3

Serious Eye Damage/Eye Irritation - Category 2A

Carcinogenicity - Category 2

Toxic to reproduction (Fertility) - Category 2

Toxic to reproduction (Unborn child) - Category 2

Skin Sensitization - Category 1

Specific Target Organ toxicity – (REPEATED EXPOSURE) - (Liver, Kidney, Central nervous system) - Category 2

Aspiration Hazard - Category 1

## 2. Hazards Identification - continued

### GHS Label Elements

Hazard pictograms:



**Signal Word**

Danger

### Hazard Statements:

Flammable liquid and vapor.  
Harmful if inhaled.  
May be fatal if swallowed and enters airways.  
Suspected of damaging fertility or the unborn child.  
Suspected of causing cancer.  
May cause allergic skin reaction  
Causes serious eye irritation.  
Vapors are irritating to eyes and respiratory tract.  
Causes damage to organs through prolonged or repeated exposure.  
(Central Nervous System (CNS)).

### Precautionary Statements - Prevention:

Obtain special instructions before use.  
Do not handle until all safety precautions have been read and understood.  
Wear protective gloves and clothing. Wear eye and face protection.  
Contaminated work clothing must not be allowed out of the workplace.  
Keep away from heat, sparks, open flames, hot surfaces and other sources of ignition. No smoking.  
Use explosion-proof electrical, ventilating, lighting and all material-handling equipment.  
Use only non-sparking tools. Keep containers tightly closed.  
Take precautionary measures against static discharge.  
Ground/bond container and receiving equipment.  
Do not breathe dust, fumes, mist, gas, vapors or spray.  
Do not eat, drink or smoke when using this product.  
Wash face, hands and any exposed skin thoroughly after handling.  
Use only outdoors or in well-ventilated area.  
In case of inadequate ventilation wear respiratory protection. The type of respiratory protection selected must comply with the requirements set forth in OSHA's Respiratory Protection Standard (29CFR 1910.134) or regional standards. For additional details, see section 8 of the SDS.

## 2. Hazards Identification - continued

### Precautionary Statements - Response:

Get medical attention if you feel unwell.

If exposed or concerned get medical attention.

**Ingestion:** Seek medical attention immediately. Do not induce vomiting. Never give anything by mouth to an unconscious person.

**Skin Contact:** IF ON SKIN (or hair): Take off all contaminated clothing immediately. Wash with plenty of soap and water. Seek medical attention if irritation develops. Wash saturated clothing and clean shoes before reuse.

**Inhalation:** IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms: Call a doctor or emergency medical facility (i.e. 911). Give artificial respiration if necessary.

**Eye Contact:** Immediately flush with large quantities of water for 15 minutes. Remove contacts if present and easy to do. Continue rinsing. If irritation persists, seek medical attention.

**Fire:** IN CASE OF FIRE: Extinguishing media: carbon dioxide, dry chemical, foam.

### Precautionary Statements - Storage

Store locked up. Keep away from heat, sparks and open flame. Keep containers tightly closed. Store away from strong oxidizing agents in a cool dry place with adequate ventilation.

### Precautionary Statements - Disposal:

Dispose of contents and container in accordance with local, county, state and federal regulations.

### Other Hazards

1. Harmful if inhaled. Repeated and prolonged occupational overexposure to solvents may cause irritation of the respiratory system and permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Inhalation of vapors above the recommended exposure limits causes central nervous depression and weakness with headaches, narcosis, nausea, dizziness, vomiting, uncoordinated or strange behavior or unconsciousness. Can also cause nasal discharge, hoarseness, coughing, chest pain and breathing difficulty.

2. Avoid contact with the skin and clothing. Harmful if absorbed through skin. Wash thoroughly after handling.

3. Ingestion can cause irritation of the digestive tract, nausea, vomiting and diarrhea. In severe cases ingestion can be fatal. Aspiration into the lungs can cause chemical pneumonitis which can be fatal.

4. Emits toxic fumes when heated.

5. Sanding and grinding dusts may be harmful if inhaled.

### Danger

Rags, steel wool or waste soaked with this product may spontaneously catch fire if improperly discarded. Immediately after each use place rags, steel wool or waste in a sealed water-filled metal container.

## 3A. Composition/ Information on Ingredients

ALL THE PRODUCTS CONTAIN ALIPHATIC DISTILLATE (CAS# 8052-41-3)

CHEMICAL NAME	CAS #	WEIGHT %	(TLV-TWA)	-----EXPOSURE LIMITS-----			
				TLV-STEL	PEL-TWA	PEL -CEILING	SKIN
ALIPHATIC DISTILLATE	8052-41-3	21 - 35	100 PPM	NO INFO	500 PPM	NO INFO	NO

(SEE SECTION 16 FOR ABBREVIATION LEGEND)

### 3B. Composition/ Information on Ingredients

THE FOLLOWING PRODUCTS CONTAIN TITANIUM DIOXIDE (CAS #13463-67-7)  
CHROME YELLOW LL, L, M - C.P. GREEN L, D, - EMERALD GREEN - FLAKE WHITE  
FRENCH YELLOW OCHRE - FRENCH ZINC WHITE - PERMANENT BLUE  
PERMANENT STRIPING WHITE - RAW SIENNA

CHEMICAL NAME	CAS #	WEIGHT %	(TLV-TWA)	-----EXPOSURE LIMITS-----			
				TLV-STEL	PEL-TWA	PEL -CEILING	SKIN
TITANIUM DIOXIDE	13463-67-7	1 - 35	10 mg/M3	NO INFO	15 mg/M3	15 mg/M3	NO

(SEE SECTION 16 FOR ABBREVIATION LEGEND)

### 3C. Composition/ Information on Ingredients

THE FOLLOWING PRODUCTS CONTAIN ETHYLENE GLYCOL MONOBUTYL ETHER (CAS# 111-76-2)  
CHROME YELLOW LL, L, M, O - C.P. GREEN L, M, - COBALT BLUE - PERMANENT BLUE  
POSTER RED - PRUSSIAN BLUE - ROSE PINK - SIGNCRAFT RED - ULTRAMARINE BLUE  
VAN DYKE BROWN

CHEMICAL NAME	CAS #	WEIGHT %	(TLV-TWA)	-----EXPOSURE LIMITS-----			
				TLV-STEL	PEL-TWA	PEL -CEILING	SKIN
ETHYLENE GLYCOL MONOBUTYL ETHER	111-76-2	1 - 3	25 PPM	50 PPM.	50 PPM.	N.E.	NO

(SEE SECTION 16 FOR ABBREVIATION LEGEND)

### 3D. Composition/ Information on Ingredients

THE FOLLOWING PRODUCTS CONTAIN IRON (III) OXIDE (CAS# 1309-37-1)  
VENETIAN RED

CHEMICAL NAME	CAS #	WEIGHT %	(TLV-TWA)	-----EXPOSURE LIMITS-----			
				TLV-STEL	PEL-TWA	PEL -CEILING	SKIN
IRON (III) OXIDE	1309-37-1	10 - 20	5 mg/M3	N. E.	5 mg/m3	N. E.	NO

(SEE SECTION X FOR ABBREVIATION LEGEND)

### 3E. Composition/ Information on Ingredients

THE FOLLOWING PRODUCTS CONTAIN INORGANIC OXIDE (CAS# 51274-00-1)  
BURNT SIENNA - BURNT UMBER - C.P. GREEN L, M, D - FRENCH YELLOW OCHRE - RAW UMBER

CHEMICAL NAME	CAS #	WEIGHT %	(TLV-TWA)	-----EXPOSURE LIMITS-----			
				TLV-STEL	PEL-TWA	PEL -CEILING	SKIN
INORGANIC OXIDE	51274-00-1	1 - 35	5 mg/M3	N. E.	10 mg/m3	N. E.	NO

(SEE SECTION 16 FOR ABBREVIATION LEGEND)

### 3F. Composition/ Information on Ingredients

THE FOLLOWING PRODUCTS CONTAIN CRYSTALLINE SILICA (CAS# 14808-60-7)  
BURNT SIENNA

CHEMICAL NAME	CAS #	WEIGHT %	(TLV-TWA)	-----EXPOSURE LIMITS-----			
				TLV-STEL	PEL-TWA	PEL -CEILING	SKIN
CRYSTALLINE SILICA	14808-60-7	1	.1 mg/M3	N. E.	.1 mg/m3	N. E.	NO

(SEE SECTION 16 FOR ABBREVIATION LEGEND)

### 3G. Composition/ Information on Ingredients

THE FOLLOWING PRODUCTS CONTAIN MANGANITE (CAS# 1317-34-6)  
RAW UMBER

CHEMICAL NAME	CAS #	WEIGHT %	(TLV-TWA)	-----EXPOSURE LIMITS-----			
				TLV-STEL	PEL-TWA	PEL -CEILING	SKIN
MANGANITE	1317-34-6	1 - 2	5 mg/M3	N. E.	.N. E.	N. E.	NO

(SEE SECTION 16 FOR ABBREVIATION LEGEND)

### 3H. Composition/ Information on Ingredients

THE FOLLOWING PRODUCTS CONTAIN AROMATIC DISTILLATE (CAS# 1330-20-7)  
VAN DYKE BROWN

CHEMICAL NAME	CAS #	WEIGHT %	(TLV-TWA)	-----EXPOSURE LIMITS-----			
				TLV-STEL	PEL-TWA	PEL -CEILING	SKIN
AROMATIC DISTILLATE	1330-20-7	1 - 2	100 PPM	150 PPM	NO INFO	NO INFO	NO

(SEE SECTION 16 FOR ABBREVIATION LEGEND)

### 3I. Composition/ Information on Ingredients

THE FOLLOWING PRODUCTS CONTAIN CARBON BLACK (CAS# 1333-86-4)  
REFINED LAMP BLACK - SOLID COVERING LAMPBLACK

CHEMICAL NAME	CAS #	WEIGHT %	(TLV-TWA)	-----EXPOSURE LIMITS-----			
				TLV-STEL	PEL-TWA	PEL -CEILING	SKIN
CARBON BLACK	1333-86-4	3 - 7	3.5 mg/M3	N. E.	3.5 mg/M3	N. E.	NO

(SEE SECTION 16 FOR ABBREVIATION LEGEND)

#### **4. First Aid Measures**

If ingestion, irritation, any type of over-exposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately. Have the Safety Data Sheet information available. Never give anything by mouth to an unconscious or convulsing person.

**Eye Contact:** Immediately flush eyes with large quantities of water for at least 15 minutes. Use lukewarm water if possible. Use fingers to insure that eyelids are separated and that the eye is being irrigated. Then remove contact lenses if easily removable, and continue eye irrigation for not less than 15 minutes. Get medical attention if irritation develops.

**Inhalation:** Remove to fresh air far from further exposure. Keep person warm and at rest. If symptoms persist, call a physician. If not breathing, give artificial respiration. Call a physician immediately.

**Ingestion:** Clean mouth with water and afterwards give plenty of water. Do not induce vomiting without medical advice. Seek medical attention immediately. Never give anything by mouth to an unconscious or convulsing person.

**Skin Contact:** Immediately remove contaminated clothing and shoes. Wash off skin with soap and water. Use lukewarm water if possible. Wash contaminated clothing and clean shoes before reuse. Get medical attention if irritation develops and persists.

#### **MOST IMPORTANT SYMPTOMS/EFFECTS**

##### **Potential Acute Health Effects**

**Eye Contact:** Causes serious eye irritation.

**Inhalation:** No known significant effects or critical hazards.

**Skin Contact:** Defatting to the skin. May cause skin dryness and irritation.

**Ingestion:** No known significant effects or critical hazards.

##### **Over-exposure Signs/Symptoms**

**Eye Contact:** Adverse symptoms may include the following: Pain or irritation, watering, redness.

**Inhalation:** Adverse symptoms may include the following: Reduced fetal weight, increase in fetal deaths, skeletal malformations.

**Skin Contact:** Adverse symptoms may include the following: Skin dryness, cracking and irritation, reduced fetal weight, increase in fetal deaths, skeletal malformations.

**Ingestion:** Adverse symptoms may include the following: Reduced fetal weight, increase in fetal deaths, skeletal malformations.

##### **Indication of Immediate Medical attention and Special Treatment Needed, If Necessary**

**Notes to Physician:** Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

**Specific Treatments:** No specific treatment.

**Protection of First-aiders:** No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

## 5. Fire-Fighting Measures

### **EXTINGUISHING MEDIA**

**Suitable Extinguishing Media:** carbon dioxide, dry chemical, foam or water spray.

**Unsuitable Extinguishing Media:** Do not use water jet.

**Special Hazards Arising From The Chemical:** Flammable liquid and vapor. Vapors can travel to a source of ignition and flash back. Can form explosive mixtures at temperatures at or above the flashpoint. “Empty” containers retain product residue (liquid and/or vapor) and can be dangerous. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND OR EXPOSE SUCH CONTAINERS TO HEAT, FLAMES, SPARKS, STATIC ELECTRICITY OR OTHER SOURCES OF IGNITION. THEY MAY EXPLODE AND CAUSE INJURY OR DEATH. Keep containers tightly closed. Closed containers may explode when exposed to extreme heat. Isolate from heat, sparks and open flame. Vapors are heavier than air and may travel along the ground or may be moved by ventilation and may be ignited by pilot lights, other flames, sparks, heaters, smoking, electric motors, static discharge or other ignition sources at locations distant from the material handling point. Eliminate or shut off **ALL** ignition sources prior to usage.

Runoff to sewer may create fire or explosion hazard. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

**Hazardous Thermal Decomposition Products:** Carbon dioxide, carbon monoxide, metal oxide/oxides.

**Protective Equipment for Firefighters:** Firefighters should wear appropriate protective equipment and a self contained breathing apparatus (NIOSH/MSHA approved or equivalent) with full face-piece operated in positive pressure mode.

**Protective Precautions for Firefighters:** Isolate area by removing all persons from the vicinity. Water may spread fire. Water spray may be used to cool containers exposed to fire. During a fire, irritating and toxic gases may be formed. Do not breathe smoke or fumes. Wear suitable protective equipment. Overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

## 6. Accidental Release Measures

**Personal Precautions, Protective Equipment and Emergency Procedures:** No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material.

**Warning!** Eliminate all ignition sources. Handling equipment must be grounded to prevent sparking. Ventilate the area. If mechanical ventilation is necessary use explosion proof ventilation. Do not breathe fumes. If exposure may or does exceed occupational exposure limits use a NIOSH/MSHA approved respirator to prevent overexposure. Avoid contact with eyes and skin. Wear suitable protective gloves, clothing and eye/face protection (see Section 8). Floor may be slippery. Use caution to prevent falling.

**Environmental Precautions:** Do not let product enter drains. Prevent further leakage or spillage if safe to do so. Keep spills and cleaning runoff out of municipal sewers and open bodies of water. If product contaminates rivers and lakes or drains inform respective authorities.

**Methods and Materials for Containment & Cleaning Up:** Dike and contain spill with inert absorbent material and place in appropriate waste container. Contaminated absorbent material may pose the same hazard as the spilled product. Dispose of product in accordance with local, county, state and federal regulations.

## 7. Handling and Storage

### **PRECAUTIONS FOR SAFE HANDLING**

**Protective Measures:** Put on appropriate protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. If exposure may or does exceed occupational exposure limits (Section 3) use a NOISH/MSHA approved respirator to prevent overexposure. Do not enter storage areas or confined spaces unless adequately ventilated. Keep in the original container. Keep tightly closed when not in use. Store and use away from heat, sparks and open flame and any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharge. Empty containers retain product residue and can be hazardous. Do not reuse container.

**Special Precautions:** Ingestion of product or cured coating may be harmful. Vapors are heavier than air and may travel along the ground or may be moved by ventilation and may be ignited by pilot lights, other flames, sparks, heaters, smoking, electric motors, static discharge or other ignition sources at locations distant from the material handling point. Eliminate or shut off **ALL** ignition sources prior to usage. Materials such as cleaning rags, paper wipes and protective clothing, which are contaminated with the product, may spontaneously self-ignite some hours later. To avoid the risk of fires, all contaminated materials should be stored in purpose-built containers or in metal containers with tight fitting self-closing lids. Contaminated materials should be removed from the workplace at the end of each working day and be stored outside.

**Hygienic Practices:** Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash with soap and water after handling and before eating, drinking, smoking or using toilet facilities. Remove contaminated clothing and protective equipment before entering eating areas. Launder contaminated clothing before reusing. Uniforms or clothing containing paint residue should not be laundered with household garments.

**Conditions for Safe Storage:** Do not store above the following temperature: 32°C (90°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool, well ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Store away from strong oxidizing agents. Keep containers tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and be kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.



## 8. Exposure Controls/Personal Protection

**Occupational Exposure Limits:** See Section 3.

### Appropriate Engineering Controls

**Engineering Measures:** Ensure adequate ventilation, especially in confined areas.

### Individual Protection Measures

**Eye/Face Protection:** Wear chemical resistant glasses and/or goggles and a face shield when eye and face contact is possible due to handling and processing of material.

**Skin and Body Protection:** Wear impervious chemical resistant gloves. Wear protective clothing as required to prevent skin contact.

**Respiratory Protection:** If exposure may or does exceed occupational exposure limits (Section 3) use a NOISH/MSHA approved respirator with organic vapor cartridge to prevent overexposure.

**Hygiene Measures:** Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash with soap and water after handling and before eating, drinking, smoking or using toilet facilities. Remove contaminated clothing and protective equipment before entering eating areas. Launder contaminated clothing before reusing. Uniforms or clothing containing paint residue should not be laundered with household garments. Ensure that eyewash stations and safety showers are close to the workstation location.

## 9. Physical and Chemical Properties

Appearance:	Liquid
Odor:	Solvent
Odor threshold:	Not available
pH:	Not available
Melting point:	Not available
Boiling point:	309°F (154°C)
Flash point:	107F° (42°C) (TCC).
Auto-ignition temperature:	Not available
Decomposition temperature:	Not available
Flammability (solid, gas):	Not available
Evaporation rate:	Slower than butyl acetate
Vapor pressure:	Not available
Vapor density:	Heavier than air
Density (lbs. /gal)	See below
Solubility in H2O:	Negligible

**9. Physical and Chemical Properties - continued**

<b><u>PRODUCT NAME</u></b>	<b>WEIGHT/GAL.</b>	<b>SPECIFIC GRAVITY</b>	<b>VOC LBS./GAL</b>	<b>VOC GR./LITER</b>
AMERICAN VERMILION	11.23	1.348	3.2	379
BULLETIN BLUE	11.13	1.336	3.4	410
BULLETIN RED	11.23	1.348	3.2	379
BURNT SIENNA	12.29	1.475	3.3	395
BURNT UMBER	11.94	1.433	3.2	387
C.P. GREEN L	11.26	1.352	3.4	409
C.P. GREEN M	11.23	1.348	3.5	419
C.P. GREEN D	13.12	1.575	3.1	366
CHROME YELLOW LL	10.84	1.301	3.5	424
CHROME YELLOW L	12.73	1.528	2.9	350
CHROME YELLOW M	11.10	1.333	3.4	403
CHROME YELLOW O	11.91	1.430	3.1	366
DROP BLACK	10.93	1.312	3.2	389
EMERALD GREEN	11.96	1.436	3.1	369
FLAKE WHITE	13.08	1.570	2.9	343
FRENCH YELLOW OCHRE	12.64	1.517	3.3	391
FRENCH ZINC WHITE	13.89	1.667	3.0	359
LIBERTY RED M	11.54	1.385	3.0	362
PERMANENT BLUE	12.87	1.545	2.8	339
PERMANENT STRIPING WHITE	13.89	1.667	3.0	359
POSTER RED	10.59	1.271	3.2	385
PRUSSIAN BLUE	11.81	1.418	3.3	398
RAW SIENNA	12.60	1.513	2.9	353
RAW UMBER	12.17	1.461	3.2	379
REFINED LAMPBLACK	10.48	1.258	3.4	405
ROSE PINK	9.98	1.198	3.1	376
SIGNCRAFT RED	10.67	1.281	3.2	386
SOLID COVERING LAMPBLACK	10.53	1.264	3.8	449
TURKEY RED	11.54	1.385	3.0	362
ULTRAMARINE BLUE	11.13	1.336	3.4	410
VAN DYKE BROWN	8.86	1.064	3.3	400
VENETIAN RED	12.10	1.453	3.6	428

## 10. Stability and Reactivity

<b>Reactivity:</b>	No dangerous reaction known under conditions of normal use.
<b>Chemical Stability:</b>	This product is stable under normal conditions.
<b>Possibility of Hazardous Reaction:</b>	Under normal conditions of storage and use, hazardous reactions will not occur.
<b>Conditions to Avoid:</b>	Heat, sparks, open flame, static electricity and sources of ignition.
<b>Incompatible materials:</b>	Keep away from strong oxidizing agents, strong alkalis and strong acids.
<b>Hazardous Decomposition Products:</b>	May produce fumes when heated to decomposition. Fumes may contain carbon monoxide, carbon dioxide and nitrogen oxides.

## 11. Toxicological Information

No toxicological studies have been conducted on this product.

## 12. Ecological Information

No studies have been conducted on this product.

## 13. Disposal Information

<b>Waste Disposal Method:</b>	Dispose of in accordance with local, state and federal regulations.
<b>Empty Container Warning:</b>	Empty containers may retain product residue. Follow label warnings even after container is emptied. Residual vapors may explode on ignition.

## 14. Transportation Information

### Land Transport (DOT)

<b>Proper Shipping Name</b>	Paint
<b>Transport Hazard Class</b>	3
<b>UN Number</b>	1263
<b>Packaging Group</b>	III

### Additional Information

**DOT:** This product may be re-classified as "Combustible Liquid" unless transported by vessel or aircraft. Non-bulk packages (less than or equal to 119 gallons) of combustible liquids are not regulated as hazardous materials in package sizes less than the product reportable quantity.

### Sea Transport (IMO/IMDG)

<b>Proper Shipping Name</b>	Paint
<b>Transport Hazard Class</b>	3
<b>UN Number</b>	1263
<b>Packaging Group</b>	III

#### 14. Transportation Information - continued

##### Air Transport (ICAO/IATA)

Proper Shipping Name	Paint
Transport Hazard Class	3
UN Number	1263
Packaging Group	III

#### 15. Regulatory Information

**TSCA: United States** All components are listed or exempt.

##### SARA 311/312

**Classification:** Fire Hazard  
Immediate (acute) health hazard  
Delayed (chronic) health

##### SARA 313

Title III of the superfund amendments and reauthorization act (SARA) has created reporting requirements for companies that handle certain chemicals and chemical categories. The following is a list of chemicals subject to the reporting requirements of SARA (40 CFR Part 372) and the products that contain those chemicals.

<u>Chemical Name</u>	<u>CAS Number</u>	<u>Weight% (max)</u>
Crystalline silica	14808-60-7)	See Section 3J

##### CALIFORNIA PROPOSITION 65

WARNING: These products and the containers they are in contain detectable amounts of one or more chemicals known to the state of California to cause cancer, birth defects or other reproductive harm. For more specific information request the California version material safety data sheet on individual products.

#### 16. Other Information

**Volatile Organic Compounds** - See Section 9.

**HMIS:** Health: 2 Flammability: 2 Reactivity: 0

The user is responsible for determining the Personal Protection Equipment Code for these products.

**LEGEND:** N. A. - Not applicable N. E. - Not established  
N. D. - Not determined

This information is furnished without warranty, express or implied. The information contained herein is, to the best of our knowledge and belief accurate. However since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. The information in this SDS relates only to the specific material designated herein.

T. J. Ronan Paint Corp. assumes no legal responsibility for use of or reliance upon the information in this SDS. It is the responsibility of the user to comply with all applicable federal, state and local laws and regulations.