

DUX Paint
A World of Color.



Dux Burnish Sealer

THE DUX BURNISH SEALERS ARE OIL BASED PIGMENTED PRIMERS THAT ELIMINATE THE REQUIREMENT FOR SEPARATE APPLICATIONS OF A SEALER OR BOLE. THEY PRODUCE A SMOOTH SURFACE REQUIRING NO OR VERY LIGHT SANDING.

BURNISH SEALERS ARE AVAILABLE IN YELLOW, RED AND GRAY THAT CAN BE INTERMIXED TO CREATE VARYING EFFECTS WITH GOLD, SILVER AND COPPER LEAF. DUE TO ITS UNIQUE FORMULATION, THE BURNISH SEALERS CAN BE USED ON MANY SUBSTRATES SUCH AS WOOD, PLASTER, METAL AND COMPOSITION SURFACES.

IT WILL SEAL THE SURFACE, PROVIDE EXCELLENT ADHESION AND PERMIT AN EASY HIGH BURNISH WITH A MINIMUM OF RUBBING.

DIRECTIONS FOR USE:

PREPARE THE SURFACE BY REMOVING ANY OILS, WAXES OR RUST. DO NOT APPLY THE BURNISH SEALER OVER LATEX OR WATERBORNE PAINTS. THE SURFACE SHOULD BE SANDED SMOOTH AND FREE OF IMPERFECTIONS.

MIX WELL BEFORE USING.

APPLY AT CONTAINER CONSISTENCY UTILIZING A SOFT NATURAL HAIR BRUSH. IF ANY THINNING IS REQUIRED, USE MINERAL SPIRITS. POROUS SURFACES MAY REQUIRE A SECOND COAT. TWO THIN COATS WILL PRODUCE BETTER RESULTS THAN ONE HEAVY COAT.

IF SANDING IS NECESSARY, USE A 320 GRIT PAPER BETWEEN COATS.

THE COATS OF BURNISH SEALER WILL DRY TO THE TOUCH IN LESS THAN ONE HOUR. IT IS BEST TO WAIT SEVERAL HOURS OR OVERNIGHT BETWEEN COATS OR BEFORE APPLYING THE GILDING SIZE.

CLEAN UP WITH MINERAL SPIRITS OR NAPHTHA THINNER.

COVERAGE: 77 SQUARE FEET PER QUART

SEE PRODUCT LABEL FOR ANY ADDITIONAL INFORMATION.