

SAFETY DATA SHEET

2 PART WOOD FILLER

Version: 4

Review date: 21/02/06

91/51/EC (2001/58/EC) - ISO 11014-1

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product name: 2 PART WOOD FILLER

Uses or/and applications: wood care

Product code nr: 731

Supplier: V 33 S.A.
Rue Croix Bernard La Muyre
F-39210 DOMBLANS CEDEX
France
Phone: +33 (3) 84 35 00 33
Fax: +33 (3) 84 44 63 18

Emergency phone number (to be used by the practising doctor): UK - National Poisons Information Service Phone: 44 / 191 22 5131
B - Centre Antipoisons Tél: 070 / 245.245

2. COMPOSITION / INFORMATION ON INGREDIENTS

Preparation name: 2 PART WOOD FILLER

Formula: FOLEE06

Component(s) contributing to the hazard:

- styrene - Id No: 601-026-00-0 - CAS no: 100-42-5 - EC no: 202-851-5
Conc. wt.(%): 15 < C <= 20 - Classification: • R 10 • Xn; R 20 • Xi; R 36/38 •
- 2-methoxy-1-methylethyl acetate - Id No: 607-195-00-7 - CAS no: 108-65-6 - EC no: 203-603-9
Conc. wt.(%): 0 < C <= 1 - Classification: • R 10 • Xi; R 36 •

3. HAZARDS IDENTIFICATION

Most important hazards: Harmful by inhalation.
Irritating to eyes and skin.
Flammable.

Specific hazards: Repeated and prolonged exposure may cause skin irritation and dermatitis due to degreasing properties of the product.
Affect many plastics.

4. FIRST AID MEASURES

General advice: In all cases of doubt, or when symptoms persist, seek medical attention.
Never give anything by mouth to an unconscious person.
In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
For symptom description, see item 11.

Inhalation: Take victim to fresh air, in a quiet place, in an half laying position and if necessary take medical advice.
Artificial respiration and/or oxygen if necessary.

Skin contact: Take off contaminated clothes, wash skin with plenty of water or have a shower (during minimum 15 minutes) and if necessary take medical advice.
Rinse with plenty of water.
If skin irritation persists, take medical advice.

Eye contact: Wash with plenty of water (during 20 minutes minimum) with eyes wide open after taking off soft contact lenses and immediately take medical advice.

Ingestion: If accidentally swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.
Rinse mouth, do not drink anything, keep quiet, and go immediately to hospital or to a doctor.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media: dry chemical powder, alcohol-resistant foam, carbon dioxide (CO₂), water spray, sand, earth.

SAFETY DATA SHEET

2 PART WOOD FILLER

Version: 4

Review date: 21/02/06

91/51/EC (2001/58/EC) - ISO 11014-1

Extinguishing media which must NOT be used for safety reasons:

Do not use a solid water stream as it may scatter and spread fire.

Specific method(s):

Cool closed containers exposed to fire with water spray.
Do not allow run-off from fire fighting to enter drains or water courses.

Specific fire hazard(s):

Explosion risks of vapours.
Vapours are heavier than air and spread above ground.
In case of fire, product decomposes in: carbon oxides (CO and CO₂) and smokes.
Concerning product toxicity, see item 11 and about product stability and reactivity see item 10.

Special protective equipment for fire-fighters:

Use a self-contained breathing apparatus and also a protective suit.

6. ACCIDENTAL RELEASE MEASURES

Personal precaution(s):

Evacuate personnel to a safe area.
Remove all sources of ignition.
Be careful to flashback of fire.
Ensure adequate ventilation.
Avoid contact with skin, eyes, or clothing.
Concerning personal protective equipment to use, see item 8.

Environmental precaution(s):

Prevent product from entering drains.
Do not allow material to contaminate ground water system.
Concerning disposal elimination after cleaning, see item 13.

Method(s) for cleaning up:

Soak up with absorbent material (for example sand, sawdust, neutral absorbent granule, silica gel).
Shovel into suitable and closed container for disposal.
Dispose as hazardous waste.

7. HANDLING AND STORAGE

Handling

- Precaution(s):

Avoid all eyes and skin contact and do not breathe vapour and mist.
Do not eat, drink and do not smoke in areas where product is used.
Shower, eyes shower and water point in proximity.
Wear personal protective equipment (see item 8).

- Technical condition(s):

Avoid static electricity discharges.
Ventilation along floor.

- Safe handling advice(s):

Keep the container tightly closed. Exclude sources of heat, sparks and open flame. Non-sparking tools should be used.
Opened containers must be carefully closed and kept upright to avoid leakage.

Storage

- Precaution(s):

Store in a place accessible by authorised persons only.
Keep container tightly closed in a cool place.

- Technical condition(s):

Not flammable and waterproof underground retention basin.

- Storage condition(s):

Keep container tightly closed and at a temperature not exceeding (°C): 45 °C
Keep away from sources of ignition - No smoking.
Store away from direct sunlight or other heat sources.
Store in a well-ventilated place.

- Separation of incompatible product(s):

Keep away from: strong bases and oxidising compounds.

- Packaging / tank material:

made of the same material as the supply container.

- Unsuitable packaging materials:

Avoid certain plastics which are soluble in product.

SAFETY DATA SHEET

2 PART WOOD FILLER

Version: 4

Review date: 21/02/06

91/51/EC (2001/58/EC) - ISO 11014-1

rubbers
aluminium

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering measure(s):

Ensure adequate ventilation, especially in confined areas.
Care about sufficient air renewal.
If these are not sufficient to maintain concentrations of particulates and/or solvent vapours below the relevant occupational exposure limits, suitable respiratory protective equipment should be worn.

Control parameter(s):

- Exposure limit(s):

• styrene:VME ppm = 50 - VME mg = 213 - VLE ppm = 100 - VLE mg = 426
• 2-methoxy-1-methylethyl acetate:VME ppm = 50 - VME mg = 275 - VLE ppm = 100 - VLE mg = 550

Personal protection equipment:

- Respiratory protection:

In case of insufficient ventilation wear suitable respiratory equipment. (breathing apparatus with filter A) Do not inhale vapour. Ventilation along the floor.

- Hand protection:

nitrile rubber gloves
neoprene gloves

- Skin and body protection:

solvent-resistant apron and boots
long sleeved protective clothing

- Eye protection:

Wear closed safety glasses. or face shield

Hygiene measure(s):

Do not eat, drink, or smoke during work.
Keep away from food, drink and animal feed.
Keep workplace clean and tidy as much as possible.

9. PHYSICAL AND CHEMICAL PROPERTIES

General information

- Physical state / form:

paste

- Colour:

brown

- Odour:

characteristic

Important health,safety and environmental information

- PH:

Not determined.

- Boiling point/range:

Not determined.

- Melting point/range:

Not applicable.

- Flash point:

35°C

- Explosion limits:

1.1 volume % < vapours < 11.5 volume %

- Relative density (water = 1):

1.04 g/cm³

- Viscosity:

Not determined.

- Water solubility:

emulsifiable

- Fat solubility:

completely soluble

- Solvent solubility:

soluble in most organic solvents

10. STABILITY AND REACTIVITY

Stability:

Stable in use and storage conditions as recommended in item 7.

Condition(s) to avoid:

Do not expose at temperatures above 45°C

Material(s) to avoid:

Avoid certain plastics which are soluble in product.
Reacts violently with: strong bases, oxidising compounds.

SAFETY DATA SHEET

2 PART WOOD FILLER

Version: 4

Review date: 21/02/06

91/51/EC (2001/58/EC) - ISO 11014-1

Hazardous decomposition products:

Hazardous decomposition products may be released during prolonged heating like smokes, carbon monoxide and dioxide.

11. TOXICOLOGICAL INFORMATION

General information(s):

There is no data available on the product itself.
Periodical medical test is recommended in function of exposition measure.

Acute toxicity

- Inhalation:

Irritating to the respiratory system, may cause throat pain and cough.
Symptoms of overexposure are dizziness, headache, tiredness, nausea, unconsciousness, breathing arrest.

- Skin contact:

Components of the product may be absorbed into the body through the skin.
Frequent or prolonged contacts may defat and dry the skin, leading to discomfort and dermatitis.
Intensive skin contact, may cause skin problems (contact dermatitis).
Poisoning possible by resorption through skin.

- Eyes contact:

Liquid splashes in the eye may cause irritation. (pain, redness) serious damage to eyes.

- Ingestion:

May cause gastrointestinal irritation, nausea, vomiting and diarrhoea.
Susceptible to induce: oedema of the lungs, heavy breathing difficulty, dizziness.

Sensitisation:

May cause sensitisation by inhalation and skin contact.

Toxicity of repeated or prolonged exposure:

Repeated and prolonged exposure may cause skin irritation and dermatitis due to degreasing properties of the product.

12. ECOLOGICAL INFORMATION

General information(s):

There is no data available on the product itself.

Persistence and degradability:

Product has only a limited biodegradability in soil and water.

Bioaccumulation:

Environmental toxicity:

Other adverse effects

13. DISPOSAL CONSIDERATIONS

Waste / unused products:

Collect all waste in suitable and labelled containers and dispose according to local legislation.
Can be recycled.
Do not dispose of waste into sewer.
Destruction by incineration / pyrolyse.

Contaminated packaging:

This container is uitsluitend bedoeld only to this product.
Container remains hazardous when empty. Continue to observe all precautions.
Wastes, including emptied containers, are controlled wastes and should be disposed of in accordance with regulations made under the Control of Pollution Act and the Environmental Protection Act.

Further Information(s):

14. TRANSPORT INFORMATION

General information(s):

Transport followed ADR, IMDG, IATA

UN N°:

1263

Land (Road / Railway: ADR/RID)

- Class:

3

- Verpakkingsgroep:

III

SAFETY DATA SHEET

2 PART WOOD FILLER

Version: 4

Review date: 21/02/06

91/51/EC (2001/58/EC) - ISO 11014-1

Sea (IMDG)

- Class: 3

Air (ICAO/IATA)

15. REGULATORY INFORMATION

Labelling:

According to european directives on classification, packaging and labelling of dangerous substances

EC number: Not applicable.

Contains: • styrene

Symbol(s): Xn - Harmful



R-phrase(s):
10 Flammable.
20 Harmful by inhalation.
36/38 Irritating to eyes and skin.

S-phrase(s):
2 Keep out of the reach of children.
25 Avoid contact with eyes.
29 Do not empty into drains.
36/37 Wear suitable protective clothing and gloves.
39 Wear eye/face protection.
46 If swallowed, seek medical advice immediately and show this container or label.
51 Use only in well-ventilated areas.

16. OTHER INFORMATION

According legislation(s):

This safety data sheet is in compliance with directives and adaptings: 91/155, 67/548, 88/379

Important remarks:

Information in this safety data sheet is based on actual knowledge in our possession and our experience.
It is recommended to pass the information of this safety data sheet, eventually in an appropriated form, to the users.
No liability will be accepted (except as otherwise provided by law) arising out of the use of information supplied in this data sheet.

Uses or/and applications: wood care

Restrictions:

This information relates to the specific material designated and may not be valid in combination with other product(s).

History

- First edition date: 26/05/99

- Previous revision date: 04/10/02

- Review date: 21/02/06

- Version: 4

- Review chapter(s) n°: 16

Written by: V33

This document was created with Win2PDF available at <http://www.daneprairie.com>.
The unregistered version of Win2PDF is for evaluation or non-commercial use only.