

Revision date : 2009/06/01 Version: 1.0

Page: 1/6 (30322588/SDS_GEN_US/EN)

1. Substance/preparation and company identification

<u>Company</u> BASF CORPORATION 100 Campus Drive Florham Park, NJ 07932, USA 24 Hour Emergency Response Information CHEMTREC: 1-800-424-9300 BASF HOTLINE: 1-800-832-HELP

2. Composition/information on ingredients

CAS Number 1309-37-1 12001-26-2 Content (W/W) 52.0 - 65.0 % 35.0 - 48.0 % <u>Chemical name</u> Iron oxide Mica-group minerals

3. Hazard identification

Emergency overview

CAUTION: PROLONGED OR REPEATED EXPOSURE MAY CAUSE LUNG DAMAGE. Avoid inhalation of dusts. Ensure adequate ventilation.

Potential health effects

Primary routes of exposure

Routes of entry for solids and liquids include eye and skin contact, ingestion and inhalation. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquified gases.

Irritation:

Inhalation of dust may cause respiratory tract irritation, coughing and breathing difficuties. Contact with the eyes or skin may cause mechanical irritation.

Repeated dose toxicity:

Prolonged and repeated exposure of dust may cause lung damage.

Medical conditions aggravated by overexposure:

Contact may aggravate pulmonary disorders.

Potential environmental effects

Aquatic toxicity:

At the present state of knowledge, no negative ecological effects are expected.

Revision date : 2009/06/01 Version: 1.0

4. First-aid measures

General advice:

Remove contaminated clothing.

If inhaled:

If difficulties occur after dust has been inhaled, remove to fresh air and seek medical attention.

If on skin:

Wash thoroughly with soap and water. If irritation develops, seek medical attention.

does not ignite

If in eyes:

Wash affected eyes for at least 15 minutes under running water with eyelids held open. If irritation develops, seek immediate medical attention.

If swallowed:

Rinse mouth and then drink plenty of water. Do not induce vomiting. Seek medical attention if necessary.

Note to physician

Treatment:

Treat according to symptoms (decontamination, vital functions), no known specific antidote.

5. Fire-fighting measures

Autoignition: Flammability: not applicable

Suitable extinguishing media: dry extinguishing media, foam

Unsuitable extinguishing media for safety reasons: carbon dioxide

Hazards during fire-fighting:

No particular hazards known.

Protective equipment for fire-fighting: Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

Further information:

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

If exposed to fire, keep containers cool by spraying with water.

6. Accidental release measures

Personal precautions:

Avoid dust formation.

Wear appropriate respiratory protection. Use personal protective clothing. Ensure adequate ventilation.

Environmental precautions:

Do not empty into drains.

Revision date : 2009/06/01 Version: 1.0 Page: 3/6 (30322588/SDS_GEN_US/EN)

This product is not regulated by RCRA. This product is not regulated by CERCLA ('Superfund').

Cleanup:

For small amounts: Pick up with suitable appliance and dispose of. For large amounts: Pick up with suitable appliance and dispose of.

Spills should be contained and placed in suitable containers for disposal.

7. Handling and storage

Handling

General advice:

Breathing must be protected when large quantities are decanted without local exhaust ventilation. Avoid contact with the skin, eyes and clothing.

Avoid dust formation. Closed containers should only be opened in well-ventilated areas.

Protection against fire and explosion:

No special precautions necessary.

See MSDS section 5 - Fire fighting measures. Prevent electrostatic charge accumulation.

Storage

General advice:

Keep in a cool place. Keep container dry.

8. Exposure controls and personal protection

Components with workplace control parameters

Iron oxide	OSHA	PEL 10 mg/m3 fumes/smoke ;
	ACGIH	TWA value 5 mg/m3 Respirable fraction;
Mica-group minerals	OSHA	TWA value 20 millions of particles per cubic foot of air ;
	ACGIH	TWA value 3 mg/m3 Respirable fraction;

Personal protective equipment

Respiratory protection:

Observe OSHA regulations for respirator use (29 CFR 1910.134). Wear a NIOSH-certified (or equivalent) organic vapour/particulate respirator.

Hand protection:

Chemical resistant protective gloves

Eye protection:

Safety glasses with side-shields.

General safety and hygiene measures:

Handle in accordance with good industrial hygiene and safety practice. Due to the colouring properties of the product closed work clothes should be used, to avoid stains during manipulation. Hands and/or face should be washed before breaks and at the end of the shift. Wash soiled clothing immediately.

9. Physical and chemical properties

Form:

Revision date : 2009/06/01

Page: 4/6
(30322588/SDS_GEN_US/EN)

Version: 1.0		(30322588/SDS_GEN_US/EN
Odour: Colour: pH value:	odourless red-brown 6.0 - 9.0	(4%(m))
Melting point:		The substance / product decomposes.
Density: Relative density: Bulk density:	3.2 g/cm3 3.2 146 kg/m3	(approx. 20 °C)
Solubility in water:	- 0, -	insoluble

10. Stability and reactivity

Hazardous reactions:

No hazardous reactions when stored and handled according to instructions. The product is chemically stable. Hazardous polymerization will not occur.

Decomposition products:

Hazardous decomposition products: No hazardous decomposition products if stored and handled as prescribed/indicated.

Thermal decomposition:

No data available.

11. Toxicological information

Acute toxicity

Oral:

LD50/rat: > 2,000 mg/kg The product has not been tested. The statement has been derived from the properties of the individual components.

Skin irritation:

May cause mechanical irritation.

Eye irritation :

May cause mechanical irritation.

12. Ecological information

Environmental fate and transport

Biodegradation:

Evaluation:

The colourant is insoluble in water and can thus be separated from water mechanically in suitable effluent treatment plant

Adsorbable organically-bound halogen (AOX):

This product contains no organically-bound halogen.

Environmental toxicity

Other ecotoxicological advice:

The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations.

Revision date : 2009/06/01 Version: 1.0

MA, NJ, PA

13. Disposal considerations

Waste disposal of substance:

Dispose of in accordance with national, state and local regulations. Do not discharge into drains/surface waters/groundwater. It is the waste generator's responsibility to determine if a particular waste is hazardous under RCRA.

Container disposal:

Uncontaminated packaging can be re-used. Packs that cannot be cleaned should be disposed of in the same manner as the contents.

14. Transport information

Land transport USDOT

Not classified as a dangerous good under transport regulations

Sea transport IMDG

Not classified as a dangerous good under transport regulations

Air transport IATA/ICAO

Not classified as a dangerous good under transport regulations

15. Regulatory information

Federal Regulations			
Registration status: TSCA, US	released / listed		
OSHA hazard category: established	Chronic target organ effects reported, OSHA PEL established, ACGIH TLV		
SARA hazard categories (EPCRA 311/312): Acute, Chronic			
State regulations			
State RTK			
CAS NumberChemica1309-37-1Iron oxide			

16. Other information

Mica-group minerals

HMIS III rating

12001-26-2

Revision date : 2009/06/01 Version: 1.0 Page: 6/6 (30322588/SDS_GEN_US/EN)

Health: 1^m Flammability: 0 Physical hazard: 0

HMIS uses a numbering scale ranging from 0 to 4 to indicate the degree of hazard. A value of zero means that the substance possesses essentially no hazard; a rating of four indicates high hazard.

Local contact information

Prod_Reg@basf.com

Mearlin® Micro Copper 9350M is a registered trademark of BASF Corporation or BASF SE IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY BASF HEREUNDER ARE GIVEN GRATIS AND BASF ASSUMES NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION. DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

Due to the merger of Engelhard Corp. and BASFGroup all Material Safety Data Sheets have been reassessed on the basis of consolidated information. This may have resulted in changes of the Material Safety Data Sheets. In case you have questions concerning such changes please contact us under the address mentioned in Section I.

END OF DATA SHEET